

Minimise Your Waste Maximise Your Savings

CS4 Static Waste Compactor

Specification

Our CS4 static compactors are mainly used for dry general waste i.e. general office waste, broken pallets, furniture, window frames, textiles, etc.



Available in a range of colours, with clear operating instructions and health and safety stickers as standard. Easy to operate, safe to use and backed by a network of our own engineers to ensure maximum reliability.



Technical Information

| Compaction Force | 32 Tonnes |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power Requirement | 32A 3Ph + N + E Socket outlet fused at 32Amp D type with local 30 Milliamp RCD protection (If you have an existing supply that doesn't match this specification, please contact technical@capitalcompactors.co.uk to check if it's usable or discuss a solution) |
| Motor | 11kW |
| Noise Level | 70dB at 3m From Unit |
| Cycle Time | 56 Seconds |
| Charge Box Volume | 3.05m ³ |
| Volume Per Stroke | 2.45m ³ |
| Ram Depth | 700mm |
| Ram Diameter | 150mm |
| Running Hydraulic Pressure | 2000psi |
| Pinning Hydraulic Pressure | 2150psi |
| Overall Length | 4271mm |
| Overall Width | 1600mm (+2520mm for Personnel Safety Enclosure) |
| Main Frame Height | 1300mm |
| Variant Shown | Side Bin Lift and Fully Enclosed Hopper with Internal Loading Door |

The details provided in our specification sheets are for your general information and use only. They are subject to change due to the continual design and build development.

Capital Compactors

Capital House, 26 Sudley Road, Bognor Regis, West Sussex PO21 1ER

www.capitalcompactors.co.uk

call +44 (0)1243 837614













Minimise Your Waste Maximise Your Savings

